



D

FLEXIBLE CONDUIT & FITTINGS

Ⓢ Liquid Tight Conduit

Material: Steel, with heavy PVC coated
Application: can be used in both dry and wet locations where it would be impractical to install EMT or other non-flexible conduit



TOPEL#	Trade Size	Metric Designator	Inside Diameter		Outside Diameter		Min. Bend Radius(mm)	Meters / Coil
			Min(mm)	Max(mm)	Min(mm)	Max(mm)		
LTC11	3/8"	12	12.29	12.80	17.50	18.00	50	100
LTC12	1/2"	16	15.80	16.31	20.80	21.30	80	100
LTC13	3/4"	21	20.83	21.34	25.20	26.70	105	50
LTC14	1"	27	26.44	27.08	32.80	33.40	165	50
LTC15	1-1/4"	35	35.05	35.81	41.40	42.20	200	25
LTC16	1-1/2"	41	40.01	40.64	47.40	48.30	225	25
LTC17	2"	53	51.31	51.94	59.40	60.30	280	20
LTC18	2-1/2"	63	62.99	63.63	72.10	73.00	370	20
LTC19	3"	78	77.98	78.74	87.90	88.90	440	10
LTC21	4"	103	101.60	102.62	113.30	114.30	600	10

Ⓢ PVC Coated Flexible Conduit


Material: Steel, with light PVC coated
Application: can be used in both dry and wet locations where it would be impractical to install EMT or other non-flexible conduit



TOPEL#	Trade Size	Metric Designator	Inside Diameter		Outside Diameter		Min. Bend Radius(mm)	Meters / Coil
			Min(mm)	Max(mm)	Min(mm)	Max(mm)		
PFC01	3/8"	12	12.29	12.80	16.70	17.20	35	100
PFC02	1/2"	16	15.80	16.31	20.20	20.70	65	100
PFC03	3/4"	21	20.83	21.34	25.50	26.10	75	50
PFC04	1"	27	26.44	27.08	31.60	32.20	100	50
PFC05	1-1/4"	35	35.05	35.81	40.80	41.50	125	25
PFC06	1-1/2"	41	40.01	40.64	46.60	47.20	150	25
PFC07	2"	53	51.31	51.94	58.10	58.70	175	20
PFC08	2-1/2"	63	62.99	63.63	71.80	72.40	200	20
PFC09	3"	78	77.98	78.74	87.20	87.90	225	10
PFC10	4"	103	101.60	102.62	111.20	112.30	275	10

Ⓢ Liquid Tight Connector Straight

Standard: UL 514B and C22.2 No. 18.3-12
Material: Zinc
Application: for use to bond liquid tight conduit to a box or enclosure



TOPEL#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
LTC-100	3/8"	35	350	1.440	1.260
LTC-15	1/2"	40	400	1.440	1.385
LTC-20	3/4"	25	250	1.562	1.720
LTC-25	1"	15	150	1.825	1.900
LTC-32	1-1/4"	*	100	2.068	2.176
LTC-38	1-1/2"	*	100	2.068	2.507
LTC-50	2"	*	60	2.103	3.178
LTC-55	2-1/2"	*	25	3.269	4.218
LTC-64	3"	*	20	4.060	4.919
LTC-75	4"	*	10	4.323	5.948

Ⓢ Liquid Tight Connector 90°

Standard: UL 514B and C22.2 No. 18.3-12
Material: Zinc
Application: for use to bond liquid tight conduit to a box or enclosure



TOPEL#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
LTCE-100	3/8"	20	200	2.055	2.335
LTCE-15	1/2"	25	250	2.215	2.345
LTCE-20	3/4"	15	150	2.545	3.550
LTCE-25	1"	10	100	2.815	3.785
LTCE-32	1-1/4"	*	50	3.360	3.960
LTCE-38	1-1/2"	*	60	3.450	4.130
LTCE-50	2"	*	25	4.035	4.700
LTCE-55	2-1/2"	*	10	5.215	5.375
LTCE-64	3"	*	10	6.100	6.500
LTCE-75	4"	*	5	6.780	8.000

D

FLEXIBLE CONDUIT & FITTINGS